

# POLY-GP ELECTRIC GROUP PUMP WITH 3HP – AUTO CLUTCH WITH SINGLE PHASE MOTOR ASSY



- It can endure big capacity / quantity of cement (min 3000kg per day)
- Mechanical auto clutch will automatically release V-belt when blockage occurred.
- Easy to move and transport
- Easy and convenience to maintain

## SPECIFICATIONS – TYPE POLY-GP ELECTRIC

SUCTION HOSE	1-1/4"
DISCHARGE BORE (Mm)	1-3/4"
DISCHARGE CAPACITY (L/Min)	1-3/4" (Capacity varies depends on grout mix)
CYLINDER DIAMETER	4 <sup>3</sup> / <sub>4</sub> "
PISTON TRAVEL	1 <sup>3</sup> / <sub>4</sub> "
DISCHARGE CAPACITY	1 <sup>3</sup> / <sub>4</sub> " G.P.M
DISCHARGE PRESSURE (Bar)	10
WEIGHT	65 IBS   111 KG
ELECTRICAL MOTOR	SINGLE PHASE 3HP
MOTOR SPEED	2850 R.P.M
SINGLE PHASE MOTOR	220KW 1-HP 240V 50Hz
POWER SOURCE	AUTO CLUTCH

### **POLYCELL SDN BHD (464311-M)**

NO. 14, JALAN PJS 1/30, TAMAN PETALING UTAMA, 46000 PETALING JAYA, SELANGOR.

Tel : +603.77834368, +603.77726259 Fax : +603.77834369

Company Web site : <http://www.polycell.com.my> email : [polycellsb@gmail.com](mailto:polycellsb@gmail.com)